

Aluminum Composite Panel Specification

COMPUESTO DE ALUMINIO

Ditta Forte S de RL de CV
Camino a la Tijera 806 Int B1, La Tijera
Tlajomulco de Zuliga Jalisco C.P 45645
www.dittaforte.com.mx
Email: contactanos@dittaforte.com.mx
Phone: (33) 1204-0664

ACM TOTAL THICKNESS RANGE:
2mm-8mm

ALUMINUM THICKNESS RANGE:
0.08mm 0.10mm 0.12mm 0.15mm 0.2mm 0.25mm 0.3mm 0.35mm 0.4mm
0.45mm 0.5mm

ACM WIDTH:
1220mm, 1250mm, 1500mm, 1550mm, 1570mm

ACM LENGTH:
Less than 6m.

COATING:

*Polyester Coating: used for digital printing.

Matt Polyester usually has better digital printing effort than Gloss Polyester

*PVDF: used for outdoor big projects. Like Alucobond, Alpolic

Warranty for PVDF is 15-20 years not change color under sunshine.

*FEVE: used for outdoor big projects. Like Alucobond, Alpolic

Warranty for PVDF is 10-15 years not change color under sunshine. All FEVE is gloss color.

PLASTIC CORE:

LDPE, low density polyethylene. It's black color

